

AVAILABLE WITH 12" iLEVEL® AT 3.5 MPH



AVAILABLE WITH 12" iLEVEL® AT 4.5 MPH



AVAILABLE WITH 12" iLEVEL® AT 3.5 MPH



AVAILABLE WITH 10" HD iLEVEL® AT 3.5 MPH



AVAILABLE WITH 10" ELEVATION AT 3.5 MPH



AVAILABLE WITH 10" ELEVATION AT 2.5 MPH



AVAILABLE WITH 10" ELEVATION® AT 3.5 MPH



	EDGE 3 STRETTO®	EDGE® 3	EDGE® 2.0	EDGE® HD	J4E	J4	J4 HD	J6	4FRONT® 2	4FRONT® 2 HD	Q1450	R-TRAK	OUTBACK	
HCPCS CODES – For more information on HCPCS code coverage, please consult our Product Planning & Reimbursement Center.														
	Group 3: Standard (K0848/K0849), Single Power (K0856/K0857), Multiple Power (K0861)	Group 3: Standard (K0848/K0849), Single Power (K0856/K0857), Multiple Power (K0861)	Group 3: Standard (K0848/K0849), Single Power (K0856/K0857), Multiple Power (K0861)	Group 3: Heavy Duty (K0850/K0851), Single Power HD (K0858), Multiple Power HD (K0862)	Group 2: Single Power (K0835)	Group 2: Standard (K0822/K0823), Single Power (K0835)	Group 2: Single Power HD (K0837)	Group 2: Standard (K0822/K0823), Single Power (K0835)	Group 3: Standard (K0848/K0849), Single Power (K0856/K0857), Multiple Power (K0861)	Group 3: Heavy Duty (K0850), Single Power HD (K0858), Multiple Power HD (K0862)	Group 3: Very HD (K0852/K0853), Single Power Very HD (K0860)	Group 3: Standard (K0848/K0849), Single Power (K0856/K0857), Multiple Power (K0861)	K0899 - Power Mobility Device, Not Coded by DME PDAC	
AVAILABLE ON VA CONTRACT	FSS Contract V797D-70001	FSS Contract V797D-70001	FSS Contract V797D-70001	FSS Contract V797D-70001	N/A	FSS Contract V797D-70001	FSS Contract V797D-70001	FSS Contract V797D-70001	FSS Contract V797D-70001	FSS Contract V797D-70001	FSS Contract V797D-70001	FSS Contract V797D-70001	Coming soon to FSS contract	Coming soon to FSS contract
WEIGHT CAPACITY ⁷	300 lbs.	300 lbs.	300 lbs.	450 lbs. ¹⁵	300 lbs.	300 lbs.	400 lbs.	300 lbs. ⁹	300 lbs.	450 lbs.	600 lbs.	300 lbs.	300 lbs: Power Positioning 350 lbs: Captain seating	
MAXIMUM SPEED ⁴	Up to 6.25 mph ¹³ (3.5 mph with iLevel®)	Up to 6.25 mph ¹³ Optional: Up to 7 mph ¹⁷	Up to 6.25 mph ¹³ (3.5 mph with iLevel®)	Up to 4.7 mph (3.5 mph with iLevel®)	Up to 5 mph (1.25 mph when)	Up to 5 mph	Up to 5 mph	Up to 4 mph	Up to 6.25 mph (3.5 mph when elevated)	Up to 5 mph (2.7 mph when elevated)	Up to 4.5 mph	Up to 7 mph (3.5 mph when elevated)	Up to 5 mph: Standard 6 mph: No Charge Option:	
GROUND CLEARANCE	2.9"	2.7" (battery tray)	2.7" (battery tray)	3" (base frame)	2.7" (battery tray)	2.9" (battery tray)	2.9" (battery tray)	2" (caster arms)	3.14" (battery tray)	3.14" (battery tray)	1.5" (anti-tip wheels)	3.97" (battery tray)	4.92" (at motors)	
TURNING RADIUS ⁵	21"	20.5"	20.5"	19.75"	20.5"	21"	21"	22"	25.9"	25.9"	26.5"	25.7"	49.2"	
LENGTH ¹¹	32.5"	35.5"	35.5"	35.6"	35.5"	35.5"	35.5"	34.74"	39.9"	39.9"	38.25"	34.8"	42"	
WIDTH	21.5" (14" drive wheels) 20.47" (12.5" drive wheels)	24.4"	24.4"	26.25"	24.4"	24.5"	24.5"	23.19"	24"	24"	29.25"	24.2"	28.82"	
DRIVE WHEELS	14" or 12.5" Pneumatic or flat free tires Optional: 14" Knobby	14" Solid Optional: 14" Pneumatic; 14" Knobby	14" Solid Optional: 14" Pneumatic; 14" Knobby	14" Run Flat Optional: 14" Pneumatic; 14" Knobby	14" Flat Free	14" Flat Free	14" Flat Free	10" Solid Optional: 10" Pneumatic	14" Flat Free Optional: 14" Pneumatic; 14" Knobby	14" Flat Free Optional: 14" Pneumatic; 14" Knobby	14" Solid	14" Solid Optional: 14" Pneumatic	15" Pneumatic	
CASTER WHEELS	Front: 5" flat free Rear: 6" flat free	Front: 6" Solid Rear: 6" Solid	Front: 6" Solid Rear: 6" Solid	Front: 6" Solid Rear: 6" Solid	Front: 6" Solid Rear: 6" Solid	Front: 6" Solid Rear: 6" Solid	Front: 6" Solid Rear: 6" Solid	Front: 5" Solid Rear: 6" Solid	Rear: 9" Flat Free	Rear: 9" Flat Free	Rear: 9" Solid	Front: 9" Solid	N/A	
ANTI-TIP WHEELS	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	Front: 4" Flat Free	Front: 4" Flat Free	Front: 4" Solid	Rear: 4" Flat Free	N/A	
BASE WEIGHT	126.4 lbs.	138.6 lbs.	138.6 lbs.	143.5 lbs.	138.5 lbs.	131.6 lbs.	131.6 lbs.	100.2 lbs.	130 lbs.	130 lbs.	195 lbs.	128 lbs.	168.6 lbs.	
BATTERY WEIGHT ¹⁴	40 AH: 31 lbs. each NF-22: 36 lbs. each	36 lbs. each	36 lbs. each	52 lbs. each	36 lbs. each	36 lbs. each	36 lbs. each	23.4 lbs. each	Group 24: 51.5 lbs. each Group 34: 44.8 lbs. each	Group 24: 51.5 lbs. each	52 lbs. each	51.5 lbs. each	58.6 lbs.	
MOTOR PACKAGES	2-pole	Standard: 2-pole Optional: 4-pole	2-pole	4-pole	2-pole	2-pole	4-pole	2-pole	4-pole	4-pole	4-pole	4-pole	4 Motor, Independent Drive	
BATTERIES ⁶	40AH (2) or NF-22 (2)	NF-22 (2)	NF-22 (2)	Group 24 (2)	NF-22 (2)	NF-22 (2)	NF-22 (2)	U-1 (2)	Group 24 (2) or Group 34 (2)	Group 24 (2)	Group 24 (2)	Group 24 (2)	Group 27	
AVAILABLE ELECTRONICS ¹²	75A QLNES 120A Q-Logic 3 75A Q-Logic NE 75A Q-Logic NE+	75A QLNES 90A QLNES 120A Q-Logic 3 75A Q-Logic NE	75A QLNES 120A Q-Logic 3 75A Q-Logic NE 75A Q-Logic NE+	120A Q-Logic 3 75A Q-Logic NE 75A Q-Logic NE+	75A QLNES 120A Q-Logic 3e 75A Q-Logic NE+	75A QLNES 75A Q-Logic NE 75A Q-Logic NE+	75A Q-Logic NE+	70A Q-Logic NE 70A Q-Logic NE+	75A QLNES 120A Q-Logic 3	120A Q-Logic 3	120A Q-Logic 3 90A VR2 6-key	75A QLNES 120A Q-Logic 3 Q-Logic NE+	120A Q-Logic 3	
SEATING SIZES														
TRU-BALANCE® 4	W: 16-22" D: 14-22"	W: 16-22" D: 14-22"	N/A	N/A	N/A	N/A	N/A	N/A	W: 16-22" D: 14-22"	N/A	N/A	N/A	N/A	
SYNERGY®	W: 10-22" D: 10-22"	W: 10-22" D: 10-22"	W: 10-22" D: 10-22"	W: 20-28" D: 15-28"	N/A	N/A	N/A	W: 10-22" D: 10-22"	N/A	N/A	W: 20-32" D: 20-28"	N/A	N/A	
TRU-BALANCE® 3 STATIC	W: 12-22" D: 12-22"	W: 12-22" D: 12-22"	W: 12-22" D: 12-22"	N/A	N/A	N/A	N/A	W: 14-20" D: 14-20"	W: 12-22" D: 12-22"	N/A	N/A	W: 12-22" D: 12-22"	N/A	
TRU-BALANCE® 3 POWER TILT	W: 12-22" D: 12-22"	W: 12-22" D: 12-22"	W: 12-22" D: 12-22"	N/A	N/A	N/A	N/A	W: 14-20" D: 14-20"	W: 12-22" D: 12-22"	N/A	N/A	W: 12-22" D: 12-22"	W: 16W-22" D16-20"	
TRU-BALANCE® 3 LIFT & TILT	W: 12-22" D: 12-22"	W: 12-22" D: 12-22"	W: 12-22" D: 12-22"	N/A	N/A	N/A	N/A	N/A	W: 12-22" D: 12-22"	N/A	N/A	W: 12-22" D: 12-22"	W: 16W-22" D16-20"	
TRU-BALANCE® 3 HD STATIC	N/A	N/A	N/A	W: 20-32" D: 20-25"	N/A	N/A	N/A	N/A	N/A	W: 20-24" D: 20-24"	N/A	N/A	N/A	
TRU-BALANCE® 3 HD POWER TILT	N/A	N/A	N/A	W: 20-32" D: 20-25"	N/A	N/A	N/A	N/A	N/A	W: 20-24" D: 20-24"	N/A	N/A	N/A	
TRU-BALANCE® 3 HD LIFT & TILT	N/A	N/A	N/A	W: 20-24" D: 20-25" ¹⁰	N/A	N/A	N/A	N/A	N/A	W: 20-24" D: 20-24"	N/A	N/A	N/A	
TRU-BALANCE® 2 HD POWER TILT	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	W: 20-32" D: 20-28"	N/A	N/A	
TRU-BALANCE® FLEX SEAT	W: 15-22" D: 15-20"	W: 15-22" D: 15-20"	W: 15-22" D: 15-20"	N/A	N/A	W: 15-22" D: 15-20"	N/A	N/A	W: 15-22" D: 15-20"	N/A	N/A	W: 15-22" D: 15-20"	N/A	
Q4 POWER LIFT & TILT	N/A	N/A	N/A	N/A	W: 16"-22" D: 16"-22"	W: 16-20" D: 16-22" Note: (Tilt Only)	W: 20-24" D: 20-24"	N/A	N/A	N/A	N/A	N/A	N/A	
Q CAPTAIN SEAT	W:16-20" D: 16-20"	W: 16-22" D: 16-22"	W: 16-22" D: 16-22"	W: 20-26" D: 18-24"	N/A	N/A	N/A	N/A	N/A	N/A	W: 22-26" D" 20-24"	W: 16-22" D: 16-22"	W: 16W-22W D16-22"	
SEAT-TO-FLOOR HEIGHTS^{13,16}														
TRU-BALANCE® 4 ⁸	18-19"	17.5-19.25"	N/A	N/A	N/A	N/A	N/A	N/A	17.75-18.75"	N/A	N/A	N/A	N/A	
SYNERGY® / STATIC ⁸	16-18" (Static only)	Synergy®: 15.875 - 20.875" Static: 16.5 - 18.5"	Synergy®: 15.875 - 20.875" Static: 16.5 - 18.5"	16.5 - 18.5"	N/A	N/A	N/A	Synergy®: 15.875-17.875" Static: 16.75"	15 - 17" (Synergy® N/A)	Static: 15-17" (Synergy® N/A)	16.5-18.5"	16-18" (Static only)	N/A	
POWER TILT ⁸	17.5-19.5"	17.5 - 19.5"	17.5-19.5"	18.5-20.5"	N/A	N/A	N/A	16.75"	17.75-19.75"	17.75-19.75"	19.5 - 20.5"	18.5-19.5"	N/A	
LIFT & TILT ⁸	18-20"	17.5 - 19.5"	17.5-19.5"	18.5 - 20.5"	N/A	N/A	N/A	N/A	17.75-19.75"	17.75-19.75"	N/A	17.25-18.25"	N/A	
TRU-BALANCE® FLEX SEAT ⁸	16.5-18.5"	16.5" - 18.25"	16.5 - 18.25"	N/A	N/A	16.5-18.25"	N/A	N/A	16.5 - 18.5"	N/A	N/A	16.5-17.5"	N/A	
Q4 POWER TILT	N/A	N/A	N/A	N/A	17.5"-19.5"	17.25-19.25"	17.25-19.25"	N/A	N/A	N/A	N/A	N/A	N/A	
Q4 LIFT & TILT	N/A	N/A	N/A	N/A	17.5"-19.5"	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
Q CAPTAIN SEAT	SSP: 16.5" - 18.5"(flex) 18"-20"(lift) Captain: 20.5"- 22.5" (flex) 22"- 24" (lift)	SSP: 16.5" - 18.25"(flex) 17.5"-19.5"(lift) Captain: 20.5"- 22.5" (flex) 21.5"- 23.25" (lift)	SSP: 16.5" - 18.25"(flex) 17.5"-19.5"(lift) Captain: 20.5"- 22.5" (flex) 21.5"- 23.25" (lift)	SSP: 16.5" - 18.5" (TB3 static) Captain: 20.5"- 22.5" (TB3 static)	N/A	N/A	SSP: 16.5" - 18.5"(flex) Captain: 20.5"- 22.5" (flex)	N/A	SSP: 17.5-22.5"(flex) 17.75-19.75"(lift) Captain: 21.75"- 22.75"(flex) 21.75"-23.75"(lift)	N/A	SSP: 18.5" - 20.5" (TB3 static) Captain: 22.5" - 24.5" (TB3 static)	SSP: 15.5-17.5" (flex) 17.25-18.25 (lift) Captain: 19.5"- 21.5" (flex) 21.25"-22.25" (lift)	Captain: 19.5" - 21.5"	

1) Standard
2) Optional
3) Requires HD Suspension
4) Speed varies with user weight, terrain type, battery charge, battery condition and tire pressure.
5) Without front rigging

6) Battery capacity may change when adding power positioning systems.
7) Weight capacity is dictated by the selection of seating.
8) All measurements +/- 1/8" with 16" x 16" seat, fixed lowers, 300 lbs. weight capacity and solid tires (add 3/8" with pneumatic tires). Depths may increase seat-to-floor height. Contact Customer Service for details. Listed measurements are in the lowest position; does not include elevating system unless specified.

9) 250 lbs. weight capacity with TRU-Balance® Systems
10) A minimum seating size of 20" x 20" is required with iLevel® on the Q6 Edge® HD; maximum seating size is 24" x 24"
11) Without foot rigging
12) All Quantum units can be ordered with specialty controls
13) 6.25 mph speed available only with Q-Logic 3.

14) Battery weight may vary +/- 3 lbs. based on manufacturer.
15) Reduced to 400 lbs. with iLevel® power adjustable seat height
16) Seat-to-floor heights are measured with the unit unloaded. Due to the 4Front's suspension system, seat-to-floor heights are approximately 0.25" lower when the unit is loaded.
17) 7 mph can only be achieved with optional 4-pole motors and Q-Logic 3. Maximum speed without 4-pole motors is 6.25 mph with Q-Logic 3.

HCPCS codes provided should not be considered as legal advice and do not guarantee reimbursement. DME providers are responsible for determining appropriate billing codes when submitting for insurance reimbursement. The information contained herein is correct at the time of publication. We reserve the right to alter specifications without prior notice.

